

IDEAL 4850-95

Power guillotine with automatic clamp and 475 mm cutting length

Electro-mechanical blade and clamp drive. Spindle guided backgauge with hand crank. Digital measurement readout for backgauge positioning (cm or inches). Optical cutting line with bright and durable LEDs. Adjustable backgauge with narrow separations and plastic gliders. Two side lays each on front and rear tables. Blade made of German high quality steel. Solid steel blade carrier and adjustable blade guides. Blade depth adjustment from the outside of the machine. Easy blade change from the front of the machine without removing covers. Automatic clamping system, guided on both sides for evenly distributed clamping pressure (clamp can be lowered or raised independently from blade). Comprehensive SCS safety package as described on pages 10/11. Solid all-metal construction. Complete with stand and storage shelf. Power supply: 230 V / 50 Hz / 1~ (other voltages available). Motor performance (input capacity): blade drive 1.1 kW, clamp drive 0.32 kW, Dimensions (H x W x D): 1230 x 755 x 970 mm, Weight: 209 kg, Colour: pearl grey.



The digital measurement readout allows an easy positioning of the backgauge. The indication accuracy of the digital display is 1/10 mm.



The electronically secured front safety guard swings out of the way easily and allows safe and convenient cutting.

Cutting length	475 mm
Cutting height	80 mm
Narrow cut	30 mm
Table depth	458 mm

