

vivid.

easymount®

EM-1650DH WIDE FORMAT LAMINATING SYSTEM

Easymount® is designed to perform and built to last.



▲ EM-1600SH

KEY FEATURES

- Laminate, mount & encapsulate in 1 system
- 3.9m/13ft a minute
- Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel
- 25mm/1" mounting thickness

GREAT FOR USE IN

- Sign makers
- Print finishers

IDEAL WHEN LAMINATING

- Posters, graphics and signs
- Mounting prints to board
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage and many more...

Scan with your smartphone to watch the video



Design & Performance

The Easymount® laminators are designed to perform and built to last.

Their advanced features allow you to laminate and mount.

Designed in-house by Vivid, the Easymount® range gives your business extra capacity by allowing you to offer your customers a complete service that you previously had to outsource.



Speed Control



Reverse Mode

Specifications

EM-1650DH

Laminating Speed (m/ft/min)	3.9m/13ft
Max. Width (mm/inches)	1650mm/65"
Mounting Thickness (mm/inches)	25mm/ 1"
Roller Diameter (mm/inches)	130mm/5"
Laminating Temperature (°C/°F)	0-130°C/32-266°F
Control Panel	Digital
Pressure Adjustment	Manual/Gauge
Film Core (mm/inches)	75mm/3"
Power Supply AC (V-Hz)	220/240-50-60
Power Consumption (W)	5150
Overall Dimensions (mm/inches)	2170x785x1255mm/85x31x49"
Gross Machine Weight (Kg/lbs)	365Kg/805lbs
Warranty	1 year

Features

- Independently heated top and bottom rollers
- Solid heavy duty construction
- Release liner take-up
- Adjustable rollers up to 20mm/0.8"
- Handy reverse mechanism
- Foot pedal for controlled operation

 /vividlaminating

 @vividlaminating

 /vividlaminating

Vivid Laminating Technologies Ltd

St George's House, Whitwick Road, Coalville, Leicestershire LE67 3FA England

0845 1 30 40 50 sales@vivid-online.com

vivid-online.com

Vivid care about the environment and is an ISO 14001 registered company.