

WIDE FORMAT LAMINATING SYSTEM

Easymount Sign Air is designed to perform and built to last.

KEY FEATURES

- Pneumatic Rollers
- Up to 5m/16ft a minute
- Heat Assist & Cold options available
- 25mm/1" mounting thickness
- Large diameter rollers
- Variable speed control
- Built-in media take-up unit
- Self gripping mandrels
- Magic eye safety feature
- Heated roller
- Single lift mechanism
- Heavy duty construction
- Release liner take-up
- Handy reverse mechanism



GREAT FOR USE IN

- Sign makers
- Print finishers

IDEAL WHEN LAMINATING

- Single banners
- Reel-to-reel laminates
- Posters, graphics and signs
- Mounting prints to boards
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage
- and many more...

Design & Performance

All the benefits of the Easymount Sign with the fantastic added benefit of pneumatic pressure control. This technology allows the roller to apply consistent pressure across the artwork to give the best finish possible. Fast and easy set up helps you to be more efficient. At the flick of a switch, your Easymount Sign Air will be ready to go.

This easy to use laminating system comprises a self-gripping mandrel and a flip-down feed tray as well as a take-up unit. Making it the perfect solution for single banners or reel-to-reel up to 50m.

Easymount Sign Air is a versatile range and is available in both 1400 and 1600 widths as well as hot and cold variants.

INCLUDES

- PNEUMATIC ROLLERS
- BUILT-IN MEDIA TAKE-UP UNIT
- SELF GRIPPING MANDRELS
- SINGLE LIFT MECHANISM

Specifications	Heat Assist		Cold	
	EM-S1400H	EM-S1600H	EM-S1400C	EM-S1600C
Laminating Speed (m/ft/min)	up to 5m/16ft	up to 5m/16ft	up to 5m/16ft	up to 5m/16ft
Max. Width (mm/inches)	1420mm/56"	1620mm/64"	1420mm/56"	1620mm/64"
Mounting Thickness (mm/inches)	25mm/1"	25mm/1"	25mm/1"	25mm/1"
Roller Diameter (mm/inches)	130mm/5"	130mm/5"	130mm/5"	130mm/5"
Laminating Temperature (°C/°F)	45°C/113°F - can be switched off	45°C/113°F - can be switched off	-	-
Pressure Adjustment	Pneumatic	Pneumatic	Pneumatic	Pneumatic
Film Core (mm/inches)	77mm/3"	77mm/3"	77mm/3"	77mm/3"
Power Supply AC (V-Hz)	220/240-50-60	220/240-50-60	220/240-50-60	220/240-50-60
Power Consumption (W)	1000	1200	38	38
Overall Dimensions (mm/inches)	1846x550x1365mm 73x22x54"	2046x550x1365mm 81x22x54"	1846x550x1365mm 73x22x54"	2046x550x1365mm 81x22x54"
Gross Machine Weight (Kg/lbs)	136Kg/300lbs	156Kg/344lbs	136Kg/300lbs	156Kg/344lbs
Gross Stand Weight (Kg/lbs)	25Kg/55lbs	30Kg/66lbs	25Kg/55lbs	30Kg/66lbs
Warranty*	1 year	1 year	1 year	1 year